

EXS

Two-Way Radio Antenna

Part Numbers (P/N):

EXS118 **EXS127**
EXS136 **EXS144**
EXS150 **EXS155**
EXS161 **EXS164**
EXS806
+ Connector Option

Features:

- Injection molded ¼ wave helical 'slim mini' antenna
- High durability, high efficiency
- Textured finish with stain-relief base
- Available in various standard connectors
- An original 'Tuf Duck' antenna

Specifications:

All Centurion products are designed for maximum efficiency and are customizable and scalable to meet your frequency and application requirements.

Frequency Range	VHF Trunking/ Cellular
Polarization	Vertical
Nominal Impedance	50 ohms
VSWR	1.5:1 max at resonance
Power Rating	50 watts
Temperature Range	-40°C to +85°C
Drop Test	1M

The EXS model antenna is available in the following frequencies and connectors.

Order by antenna model, frequency and connector. For example: EXS150MX.

Length of each antenna will vary according to the connector chosen.

Part Number	Frequency Band	Connectors	Average Length
EXS118	118-127 MHz	BNX, MX & SMV	5.1"
EXS127	127-136 MHz	BNX, MX & SMV	3.62" - 4.4"
EXS136	136-144 MHz	BNX, MX, MXI, SMI & SMV	3.62" - 4.4"
EXS144	144-148 MHz	BNX, MX & SMV	3.55" - 4.45"
EXS150	150-162 MHz	BNX, MX, MXI, SMI & SMV	3.5" - 4.39"
EXS155	155-164 MHz	BNX, MX & SMV	3.45" - 4.2"
EXS161	161-174 MHz	MXI & SMI	3.5"
EXS164	164-174 MHz	BNX, MX & SMV	3.3" - 3.95"
EXS806	806-866 MHz	SF & TN	-



EXS

Specifications subject to change without notice.

EXS 5 - 8/4/04